



**20'**  
**8' 6"**  
**HIGH**

# Refrigerated Container (Temperature Controlled Container) 20'

Construction	Inside Dimensions				Door opening		Weights			Capacity
	Length	Width	Height	Max Stowage Height	Width	Height	Max. Gross	Tare	Max. Payload	
Steelframe. Walls: outside and inside stainless steel	5,479mm 17ft 11 <sup>5/8</sup>	2,286mm 7ft 6	2,257mm 7ft 4 <sup>7/8</sup>	2,157mm 7ft 7 <sup>7/8</sup>	2,286mm 7ft 6	2,220mm 7ft 3 <sup>3/8</sup>	30,480kg 67,200lbs	3,160kg 6,970lbs	27,320kg 30,230lbs	28,3m <sup>3</sup> 1,000cu.ft
	5,459mm 17ft 10 <sup>7/8</sup>	2,295mm 7ft 6 <sup>1/8</sup>	2,268mm 7ft 6	2,168mm 7ft 1 <sup>3/8</sup>	2,291mm 7ft 6 <sup>1/8</sup>	2,259mm 7ft 4 <sup>7/8</sup>	30,480kg 67,200lbs	3,050kg 3,720lbs	27,230kg 60,480lbs	28,4m <sup>3</sup> 1,003cu.ft
	5,448mm 17ft 10 <sup>1/2</sup>	2,290mm 7ft 6 <sup>1/8</sup>	2,264mm 7ft 5 <sup>1/8</sup>	2,164mm 7ft 1 <sup>1/8</sup>	2,286mm 7ft 6	2,260mm 7ft 5	30,480kg 67,200lbs	3,060kg 6,750lbs	27,420kg 60,450lbs	28,3m <sup>3</sup> 1,000cu.ft
	5,534mm 18ft 1 <sup>7/8</sup>	2,316mm 7ft 7 <sup>3/10</sup>	2,331mm 7ft 7 <sup>3/4</sup>	2,231mm 7ft 3 <sup>3/4</sup>	2,316mm 7ft 7 <sup>3/16</sup>	2,290mm 7ft 6 <sup>3/16</sup>	30,480kg 67,200lbs	3,030kg 6,680lbs	27,450kg 60,520lbs	29,9m <sup>3</sup> 1,056cu.ft

## Description

Permissible temperature setting:

**+25°C to -25°C**

**(+77°F to -13°F).**

The set temperatures can be kept as long as the difference between the average outside temperature and the cargo temperature does not exceed the following limits:

**for heating 42°C (76°F)**

**for cooling 65°C (117°F).**